

SAFETY DATA SHEET

Tru Tension - E-Bike Drivetrain Cleaner

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Tru Tension - E-Bike Drivetrain Cleaner

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaner

1.3. Details of the supplier of the safety data sheet

Supplier Tru Tension Ltd
Sugnull Business Centre
Sugnull
Stafford
ST21 6NF
Tel: +44 (0) 1275 792114
chris@tru-tension.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 1275 792114 (Hours 09:00 - 17:00 Mon to Fri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 2 - H411

Human health Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional information on health hazards.

Environmental The product contains a substance which is toxic to aquatic organisms.

Physicochemical The product is highly flammable. Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapours may form explosive mixtures with air.

2.2. Label elements

Hazard pictograms



Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.

Tru Tension - E-Bike Drivetrain Cleaner

Precautionary statements	<p>P102 Keep out of reach of children.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P312 Call a POISON CENTRE/doctor if you feel unwell.</p> <p>P331 Do NOT induce vomiting.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Supplemental label information	RCH002b For professional users only.
Contains	HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS, NAPHTHA (PETROLEUM), HYDROTREATED HEAVY
Supplementary precautionary statements	<p>P240 Ground and bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical equipment.</p> <p>P242 Use non-sparking tools.</p> <p>P243 Take action to prevent static discharges.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P273 Avoid release to the environment.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P391 Collect spillage.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P405 Store locked up.</p>

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS	60-100%
CAS number: 64742-49-0	EC number: 927-510-4
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	

Tru Tension - E-Bike Drivetrain Cleaner

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	10-30%
CAS number: 64742-48-9	EC number: 919-857-5
Classification	
Flam. Liq. 3 - H226	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	
2-BUTOXYETHANOL	5-10%
CAS number: 111-76-2	EC number: 203-905-0
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If in doubt, get medical attention promptly.
Ingestion	Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for breathing. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information	See Section 11 for additional information on health hazards.
----------------------------	--------------------------------------------------------------

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Foam, carbon dioxide or dry powder.
-------------------------------------	-------------------------------------

5.2. Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up.
-------------------------	--------------------------------------------------------------------------------------------

5.3. Advice for firefighters

Tru Tension - E-Bike Drivetrain Cleaner

Protective actions during firefighting Use water to keep fire exposed containers cool and disperse vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. Use suitable respiratory protection if ventilation is inadequate.

Advice on general occupational hygiene Wash promptly with soap and water if skin becomes contaminated. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Protect from freezing and direct sunlight. Store in a dry place. Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks and open flame.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

2-BUTOXYETHANOL

Long-term exposure limit (8-hour TWA): WEL 25 ppm 123 mg/m³

Short-term exposure limit (15-minute): WEL 50 ppm 246 mg/m³

Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS (CAS: 64742-49-0)

Tru Tension - E-Bike Drivetrain Cleaner

DNEL	Consumer - Oral; Long term systemic effects: 149 mg/kg/day
	Consumer - Dermal; Long term systemic effects: 149 mg/kg/day
	Workers - Dermal; Long term systemic effects: 300 mg/kg/day
	Consumer - Inhalation; Long term systemic effects: 447 mg/m ³
	Workers - Inhalation; Long term systemic effects: 2085 mg/m ³

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CAS: 64742-48-9)

DNEL	Workers - Dermal; Long term systemic effects: 208 mg/kg/day
	Workers - Inhalation; Long term systemic effects: 871 mg/m ³
	Consumer - Dermal; Long term systemic effects: 125 mg/kg/day
	Consumer - Inhalation; Long term systemic effects: 185 mg/m ³
	Consumer - Oral; Long term systemic effects: 125 mg/kg/day

2-BUTOXYETHANOL (CAS: 111-76-2)

DNEL	Industry - Dermal; Short term systemic effects: 89 mg/kg/day
	Industry - Inhalation; Short term systemic effects: 1091 mg/m ³
	Industry - Inhalation; Short term local effects: 246 mg/m ³
	Industry - Dermal; Long term systemic effects: 125 mg/kg/day
	Industry - Inhalation; Long term systemic effects: 98 mg/m ³
	Consumer - Inhalation; Short term systemic effects: 426 mg/m ³
	Consumer - Oral; Short term systemic effects: 26.7 mg/kg/day
	Consumer - Dermal; Short term systemic effects: 89 mg/kg/day
	Consumer - Dermal; Long term systemic effects: 75 mg/kg/day
	Consumer - Inhalation; Long term local effects: 147 mg/m ³
	Consumer - Inhalation; Long term systemic effects: 59 mg/m ³
	Consumer - Oral; Long term systemic effects: 6.3 mg/kg/day

PNEC	- Fresh water; 8.8 mg/l
	- marine water; 0.88 mg/l
	- Sediment (Freshwater); 8.14 mg/kg
	- Sediment (Marinewater); 3.46 mg/kg
	- Soil; 2.8 mg/kg
	- STP; 463 mg/l

8.2. Exposure controls

Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.
Hand protection	The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.
Other skin and body protection	Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist.
Respiratory protection	No specific recommendations. If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Light brown.
Odour	Solvent.

Tru Tension - E-Bike Drivetrain Cleaner

Odour threshold	No information available.
pH	No information available.
Melting point	No information available.
Initial boiling point and range	94 (94 to 215)°C @
Flash point	-5°C Closed cup.
Evaporation rate	No information available.
Evaporation factor	No information available.
Flammability (solid, gas)	No information available.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.6 % Upper flammable/explosive limit: 10.6 %
Vapour pressure	No information available.
Vapour density	No information available.
Relative density	0.757
Solubility(ies)	Insoluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	230°C
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	No information available.
Oxidising properties	No information available.
<u>9.2. Other information</u>	
Other information	None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability The product may not be stable under some conditions of storage or use.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None known.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid None known.

10.6. Hazardous decomposition products

Tru Tension - E-Bike Drivetrain Cleaner

Hazardous decomposition products None at ambient temperatures.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 19,402.99

Acute toxicity - dermal

ATE dermal (mg/kg) 16,417.91

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 164.18

Inhalation May cause drowsiness or dizziness. Vapours in high concentrations are narcotic. Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion May be fatal if swallowed and enters airways.

Skin contact Causes skin irritation.

Eye contact Particles in the eyes may cause irritation and smarting.

Acute and chronic health hazards No known chronic or acute health risks.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Toxicological information on ingredients.

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,001.0

Species Rat

ATE oral (mg/kg) 5,001.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,001.0

Species Rabbit

ATE dermal (mg/kg) 2,001.0

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,001.0

Species Rat

ATE oral (mg/kg) 5,001.0

Acute toxicity - dermal

Tru Tension - E-Bike Drivetrain Cleaner

Acute toxicity dermal (LD₅₀ 3,001.0 mg/kg)

Species Rabbit

ATE dermal (mg/kg) 3,001.0

2-BUTOXYETHANOL

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 1,300.0 mg/kg)

Species Rat

ATE oral (mg/kg) 1,300.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,001.0 mg/kg)

Species Guinea pig

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 11.0

Species Rat

ATE inhalation (vapours mg/l) 11.0

SECTION 12: Ecological information

12.1. Toxicity

Ecological information on ingredients.

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS

Acute aquatic toxicity

Acute toxicity - fish NOEC, : 1.534 mg/l, Fish
LC₅₀, 96 hours: >13.4 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates NOEC, : 1 mg/l, Daphnia magna
LC₅₀, 48 hours: 3 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 10 mg/l, Algae

Acute toxicity - microorganisms LOEC, : 1-10 mg/l, Activated sludge

2-BUTOXYETHANOL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 1474 mg/l, Oncorhynchus mykiss (Rainbow trout)

Tru Tension - E-Bike Drivetrain Cleaner

Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 1550 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 1840 mg/l, Algae NOEC, 72 hours: 130 mg/l, Algae
<u>Chronic aquatic toxicity</u>	
Chronic toxicity - aquatic invertebrates	NOEC, 21 days: 100 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability No data available.

Ecological information on ingredients.

2-BUTOXYETHANOL

Persistence and degradability	The product is readily biodegradable.
Biodegradation	- Degradation 90.4%: 28 days

12.3. Bioaccumulative potential

Partition coefficient No information available.

12.4. Mobility in soil

Mobility No data available

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Dispose of waste product or used containers in accordance with local regulations Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Disposal methods	Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not pierce or burn, even after use.
Waste class	The waste code classification is to be carried out according to the European Waste Catalogue (EWC).

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1993
UN No. (IMDG)	1993
UN No. (ICAO)	1993
UN No. (ADN)	1993

Tru Tension - E-Bike Drivetrain Cleaner

14.2. UN proper shipping name

Proper shipping name (ADR/RID) FLAMMABLE LIQUID, N.O.S.

Proper shipping name (IMDG) FLAMMABLE LIQUID, N.O.S.

Proper shipping name (ICAO) FLAMMABLE LIQUID, N.O.S.

Proper shipping name (ADN) FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group II

IMDG packing group II

ICAO packing group II

ADN packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 2

Emergency Action Code •3YE

Hazard Identification Number (ADR/RID) 33

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical safety assessment

Tru Tension - E-Bike Drivetrain Cleaner

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	04/12/2020
Revision	1
SDS number	8943
Hazard statements in full	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.